



Restore-X®
EXTERIOR FINISH REMOVER
03Y700
PRODUCT DATA SHEET

CHARACTERISTICS

Restore-X® 03Y700 Exterior Finish Remover is uniquely formulated to remove most heavy-bodied weathered exterior wood stains and paints without having to scrape or sand the surface. **Finish Remover** also removes soil deposits and graying effects from weathering, while restoring the natural beauty of the wood. It is a biodegradable and non-flammable product that will not harm the environment when used as directed.

Finish Remover is recommended for exterior use on wood siding, composite wood siding, wood decking, furniture, fencing, railings, steps and other exterior cement surfaces such as stucco, brick and concrete.

SPECIFICATIONS

Appearance.....Green Liquid Gel
Composition.....Sodium Hydroxide
Solvents.....Ethylene Glycol
Weight.....8.72 lbs./gal.
Stability.....Stable to 32°F (0°C)
If freezing occurs, thaw and stir product.
VOC.....217 grams/liter
PH.....12-13
Coverage.....175-300 ft²/gal.
Depending on surface texture & coat thickness
Containers.....1 and 5 Gal. pails
Flammability.....Non-Flammable
Solubility.....Water Soluble
Environmental..... Biodegradable, Non-Toxic

SURFACE PREPARATION

Read all instructions before beginning. Always run a small test patch area first. This will help you learn how much time and how much **Finish Remover** it will take to complete your project.

Remove excess dirt and debris with a stiff bristled broom, pressure washer or by other methods.

Protect all metal surfaces especially bare and anodized aluminum surfaces (such as doors and

window frames) by masking with silver duct tape to prevent discoloration or removal of any anodized coating. To protect any nearby plants, shrubs or other vegetation wet them down with water and cover with a plastic sheet before application. Thoroughly wet the surface with clean water and remove any standing water.

APPLICATION

Apply the **Finish Remover** in a thick, liberal coat with a synthetic brush or roller. Thin coats are not as effective. **DO NOT SPRAY.** Do not allow exposed surfaces treated with **Finish Remover** to dry out. As needed, lightly mist the working area with water. Do not apply if the product, ambient air, or substrate temperature is below 45°F (7°C).

Wait! It is very important to allow **Finish Remover** time to dissolve the deteriorated stains and paint. Latex paints may take considerably longer than Oil based paints. Expect some variation in removal time. The length of time required for **Finish Remover** to work will depend on air temperature, amount of product applied, condition of the surface being treated and keeping the work area damp. Regularly check a small section of your surface to control the extent of treatment. Removal times can vary from 15 minutes to four (4) hours. If leaving project over night, cover project with 1 mil thick plastic sheeting to keep wood moist and reduce evaporation.

REMOVAL: Test a small area by using a scrub brush to see if the finish is ready for removal. When ready, agitate the surface with a firm nylon bristled brush, or a long handled push broom for larger areas, and rinse thoroughly using high pressure water from a garden hose or a pressure washer.

STUBBORN AREAS MAY REQUIRE ADDITIONAL APPLICATIONS.

CLEANUP INFORMATION (OVER)



Restore-X®
EXTERIOR FINISH REMOVER
03Y700
PRODUCT DATA SHEET

When applying and rinsing this product walking surfaces, ladders, and scaffolding may become slippery. Clean spills and spatters immediately with soap and warm water. Clean hands, tools, equipment and clothing with soap and warm water. Use clean water to hose off any plants, shrubs or other contaminated vegetation.

SAFETY

This product contains solvents and/or other chemical ingredients. Adequate health safety precautions should be observed during storage, handling, use and drying periods.

Use wrap-around goggles, other appropriate chemical eyewear protection, non-permeable rubber gloves, and other appropriate clothing protection when using Restore-X® 03Y700 Exterior Wood Deck Cleaner.

READ MATERIAL SAFETY DATA SHEETS BEFORE USING THIS PRODUCT

CAUTION

Keep away from children, pets and other animals. Protect from freezing. This product contains sodium hydroxide and other chemical ingredients. Adequate health and safety precautions should be observed during storage, handling, use and drying periods. Use with adequate ventilation. Do not mix product with any other materials, detergents or any other additives.

LIMITATIONS

The technical data and suggestions for use in this product data sheet are currently correct to the best of our knowledge, but are subject to change without notice. Because application and conditions vary, and are beyond our control, we are not responsible for results obtained in using this product, even when used as suggested. The user should conduct tests to determine the suitability of the product for the intended use (including liability for breach of warranty, strict liability in tort, negligence or otherwise) is limited exclusively to replacement of the product or refund of its price. Under no circumstance are we liable for incidental and consequential damages.

This supersedes previous data sheets for this product.
Revised 5/8/06