

PRODUCT DATA SHEET
PEEL SEAL
86D000 CLEAR

CHARACTERISTICS

86D000 Peel Seal is a clear, flexible sealer designed to bond existing peeling, chalking, or cracking paint prior to recoating the surface. Use over most interior and exterior surfaces. Masonry products must be completely cured to prevent trapping moisture behind the painted surface. Not for use on flooring, decking or continued water immersion.

PHYSICAL PROPERTIES

Appearance: Milky White Liquid
Viscosity: 20-25 sec. Zahn cup #3
% Solids Wt. /Vol: 30-33%
VOC: <1 lb. /gal.
Drytime: 1-2 hrs. Recoat 2-3 hrs.
PVC: 6%
Wt. /Gal.: 8.8 lbs.
PH: 8.5-9.0
Coverage: 275-375 sq ft. /gal.

APPLICATION

Apply by spray, roll or brush. Do not reduce with water at any time, use as supplied. Coverage will vary with the method of application.

PRIMER/TOPCOATING

Prime and topcoat with Forrest 95J000 Exterior, 84IQ100 Interior Latex primers or Forrest 3000 Oil Alkyd primer. Apply Forrest interior or exterior acrylic topcoats for best results.

SAFETY

This product contains solvents and/or other chemical ingredients. Adequate health and safety precautions should be observed during storage, handling, use and drying periods.

**READ MATERIAL SAFETY DATA SHEETS
BEFORE USING THIS PRODUCT.**

LIMITATIONS

The technical data and suggestions for use in this product data sheet are currently correct to the best of our knowledge, but are subject to change without notice. Because application and conditions vary, and are beyond our control, we are not responsible for results obtained in using this product, even when used as suggested. The user should conduct tests to determine the suitability of the product for the intended use (including liability for breach of warranty, strict liability in tort, negligence or otherwise) is limited exclusively to replacement of the product or refund of its price. Under no circumstance are we liable for incident-al and consequential damages.

"Revised 04/22/03 (rp). Supersedes all previous product data sheets for this product."