

PRODUCT DATA SHEET

TEXTURED COATING MONSTER GRIP PAINT AEROSOL MG1A29E EPOXY

CHARACTERISTICS

Monster Grip Paint is an epoxy ester type coating containing non-skid recycled plastic particles specifically designed to give a hard textured coating for foot traffic on steel, fiber glass, treated aluminum, concrete, and properly primed wood substrate. Ideal for boat, trailer, laundry room, bathroom, on steps, ramps, and a variety of industrial and residential applications.

SURFACE PREPARATION

Surface should be dry, clean and free from contaminants such as oil, wax, dirt, or mill scale. Aluminum surfaces should be treated first before applying the coating. Wood surfaces should be primed with Oil Base primer.

APPLICATION

Apply at temperatures 50°- 90°F. Dries to touch in 10-20 minutes. Dry hard in 24 hrs. or more depending on weather conditions. Do not subject to foot traffic in less than 24 hours on drying time. This product is not recommended for garage floors, nor for wood surfaces subjected to standing water.

PHYSICAL PROPERTIES

Vehicle	Epoxy Ester
Weight per gallon	6.84 #/Gal.
Solid weight %	23 - 26%
Solid volume %	12 - 14%
Dry to touch	10-20 minutes at 77° F.
Dry hard	24 hours at 77°F.
Theoretical Coverage	70 sq. ft. per gallon @ 3 mil dry film thickness

PRIMER

Where needed, a non-lifting solvent base primer may be applied for added corrosion resistance.

CLEANUP

Thinner, Toluene, Xylene, or Lacquer thinner.

COLORS

1A29E104-White	1A29E000-Clear
1A29E601-Safety Orange	1A29E201-Black
1A29E702-Sequoia Green	1A29E400-Blue
1A29E804-Umber Brown	1A29E806-Chamois
1A29E501-Safety Yellow	1A29E805-Butternut
1A29E902-Shipstone Gray	
1A29E301-Russett Red	

SAFETY

This product contains solvents and or other chemical ingredients. Adequate health and safety precautions should be observed during all storage, handling, use and drying periods.

**READ MATERIAL SAFETY DATA SHEET
BEFORE USING THIS PRODUCT.**

LIMITATIONS

The technical data and suggestions for use in this product data sheet are currently correct to the best of our knowledge, but are subject to change without notice. Because application and conditions vary, and are beyond our control, we are not responsible for results obtained in using this product, even when used as suggested. The user should conduct tests to determine the suitability of the product for the intended use under then existing conditions. Any liability we may have with respect to a product or its use (including liability for breach of warranty, strict liability in tort, negligence or otherwise) is limited exclusively to replacement of the product or refund of its price. Under no circumstances are we liable for incidental and consequential damages.